

d= 25cm

This architectural drawing shows a detailed floor plan of a building, likely a residential or institutional structure. The plan is oriented with North at the top. It features a central corridor system with multiple rooms and service areas. Key elements include:

- Rooms and Areas:** Various rooms are labeled with numbers and dimensions, such as 1 (10/15), 2 (2 x 21/10/15), 3 (11/10/15), 4 (12/14/15), 5 (6/10/15), 6 (2 x 22/10/15), 7 (2 x 21/10/15), 8 (2 x 20/15), 9 (14/14/15), 10 (6/10/15), 11 (2 x 12/14/15), 12 (2 x 12/14/15), 13 (2 x 12/14/15), 14 (2 x 12/14/15), 15 (2 x 12/14/15), 16 (2 x 12/14/15), 17 (2 x 12/14/15), 18 (2 x 12/14/15), 19 (2 x 12/14/15), 20 (2 x 12/14/15), 21 (2 x 12/14/15), 22 (2 x 12/14/15), 23 (2 x 12/14/15), 24 (2 x 12/14/15), 25 (2 x 12/14/15), 26 (2 x 12/14/15), 27 (2 x 12/14/15), 28 (2 x 12/14/15), 29 (2 x 12/14/15), 30 (2 x 12/14/15), 31 (2 x 12/14/15), 32 (2 x 12/14/15), 33 (2 x 12/14/15), 34 (2 x 12/14/15), 35 (2 x 12/14/15), 36 (2 x 12/14/15), 37 (2 x 12/14/15), 38 (2 x 12/14/15), 39 (2 x 12/14/15), 40 (2 x 12/14/15), 41 (2 x 12/14/15), 42 (2 x 12/14/15), 43 (2 x 12/14/15), 44 (2 x 12/14/15), 45 (2 x 12/14/15), 46 (2 x 12/14/15), 47 (2 x 12/14/15), 48 (2 x 12/14/15), 49 (2 x 12/14/15), 50 (2 x 12/14/15), 51 (2 x 12/14/15), 52 (2 x 12/14/15), 53 (2 x 12/14/15), 54 (2 x 12/14/15), 55 (2 x 12/14/15), 56 (2 x 12/14/15), 57 (2 x 12/14/15), 58 (2 x 12/14/15), 59 (2 x 12/14/15), 60 (2 x 12/14/15), 61 (2 x 12/14/15), 62 (2 x 12/14/15), 63 (2 x 12/14/15), 64 (2 x 12/14/15), 65 (2 x 12/14/15), 66 (2 x 12/14/15), 67 (2 x 12/14/15), 68 (2 x 12/14/15), 69 (2 x 12/14/15), 70 (2 x 12/14/15), 71 (2 x 12/14/15), 72 (2 x 12/14/15), 73 (2 x 12/14/15), 74 (2 x 12/14/15), 75 (2 x 12/14/15), 76 (2 x 12/14/15), 77 (2 x 12/14/15), 78 (2 x 12/14/15), 79 (2 x 12/14/15), 80 (2 x 12/14/15), 81 (2 x 12/14/15), 82 (2 x 12/14/15), 83 (2 x 12/14/15), 84 (2 x 12/14/15), 85 (2 x 12/14/15), 86 (2 x 12/14/15), 87 (2 x 12/14/15), 88 (2 x 12/14/15), 89 (2 x 12/14/15), 90 (2 x 12/14/15), 91 (2 x 12/14/15), 92 (2 x 12/14/15), 93 (2 x 12/14/15), 94 (2 x 12/14/15), 95 (2 x 12/14/15), 96 (2 x 12/14/15), 97 (2 x 12/14/15), 98 (2 x 12/14/15), 99 (2 x 12/14/15), 100 (2 x 12/14/15).
- Dimensions:** Various dimensions are indicated throughout the plan, such as 10/15, 12/14, 14/15, 16/15, 18/15, 20/15, 22/10, 24/15, 26/15, 28/15, 30/15, 32/15, 34/15, 36/15, 38/15, 40/15, 42/15, 44/15, 46/15, 48/15, 50/15, 52/15, 54/15, 56/15, 58/15, 60/15, 62/15, 64/15, 66/15, 68/15, 70/15, 72/15, 74/15, 76/15, 78/15, 80/15, 82/15, 84/15, 86/15, 88/15, 90/15, 92/15, 94/15, 96/15, 98/15, 100/15.
- References:** The plan includes references to other drawings: 'Siehe Plan B1001' (top left), 'Siehe Plan B1000' (top right), and 'Siehe Plan B2402' (bottom right).
- Orientation:** A North arrow is located in the upper right corner of the plan.
- Scale:** A scale bar is provided at the bottom left, indicating a length of 10 meters.

Technical drawing of a rectangular reinforced concrete slab (A) with dimensions and reinforcement details.

Dimensions:

- Overall width: 4.20 m
- Overall length: 3.88 m
- Top edge width: 3.20 m
- Bottom edge width: 2.50 m
- Left edge height: 0.75 m
- Right edge height: 0.62 m
- Bottom edge height: 0.18 m

Reinforcement Details:



- Top edge: 12 ϕ 10/15
- Bottom edge: 12 ϕ 10/15
- Left edge: 12 ϕ 10/15
- Right edge: 12 ϕ 10/15
- Internal reinforcement: 12 ϕ 10/15
- Top edge reinforcement: 12 ϕ 10/15
- Bottom edge reinforcement: 12 ϕ 10/15
- Left edge reinforcement: 12 ϕ 10/15
- Right edge reinforcement: 12 ϕ 10/15
- Internal reinforcement: 12 ϕ 10/15
- Top edge reinforcement: 12 ϕ 10/15
- Bottom edge reinforcement: 12 ϕ 10/15
- Left edge reinforcement: 12 ϕ 10/15
- Right edge reinforcement: 12 ϕ 10/15
- Internal reinforcement: 12 ϕ 10/15

[illegible]

GEWINDESTAHL-STÜCKLISTE							TYP GEWI	
POS.	STÜCK	Ø (mm)	SCHNITTLÄNGE (m)	ENDE 1	ENDE 2	GEWICHT (kg)	GESAMTLÄNGE (m)	
24	8	25	4,200	Gewinde	Muffe	16,170	33,600	
GESAMTMENGE (BETONSTAHL, BSt 500 S)							(m)	(kg)
	25	3,850				33,600		129,360
GESAMTGEWICHT								129,360

3x  HBT 190-10/15-5-1250, h=220, lü=500

SCHRAUBMUFFENVERBINDUNGEN

ABSTANDSHALTER		BÜGELSCHLOSSER	KROPPMASS
ABSTANDS-BOCKE  MIT MONTAGE-STAB	S-HAKEN  min. 2 STÜCK/m²	 BÜGELSCHLOSSER VERSCHWENKEN  S-HAKEN IN SCHALUNG ABBIEGEN	 KROPPMASS

BETONDECKUNG

UNTERSTÜTZUNGSKÖRPER

BETONDECKUNG

ABSTANDSHALTER

OBEN

UNTEN

1. LAGE

2. LAGE

3. LAGE

4. LAGE

2. LAGE

1. LAGE

Y

X

OBEN 1. LAGE

UNTEN 1. LAGE

WEITERE ANFORDERUNGEN

MINDESTWERTE DER BIEGEROLLENDURCHMESSER d_{gr} NACH DIN EN 1992-1-1/NA

[illegible]

ÜBERSICHT: ‡ 0.00 = 327.50 U. NM

